



Bf & F

Synchronised photocells, for outdoors (BF, FE); vandal resistant metal (FEP); flush-mounted (FI).

Technical characteristics:

- **unaffected by disturbance caused by sunbeams;**
- the versions for external use can be wall-mounted (no holes or grooving);
- **shockproof, polycarbonate front covers:** long-lasting and shockproof;
- **maximum safety:** to eliminate the problem of reflections from nearby objects two range levels are available: 15 m standard and 30 m.

Sel

Selector switches with personalised keys (10 codes).

In two versions:

- **externally mounted (SELE)** metal, tamper-proof container: reliability and safety, protects against tampering and damage resulting from vandalism;
- **flush-mounted (SELI)** built-in switches are both safe and strong: all the electrical and mechanical components are housed in the flush-mounted metal container set, compatible with standard, 60 mm diameter, built-in boxes.

Bf

Code	Description	Pc/Pack
BF	Pair of surface-mounted photocells	1

F

Code	Description	Pc/Pack
FE	Pair of surface-mounted photocells	1
FEP	Pair of surface-mounted photocells in vandal resistant metal	1
FI	Pair of photocells for flush mounting	1

Sel

Code	Description	Pc/Pack
SELE	Selector switch for outdoors installation	1
SELI	Selector switch for flush mounting	1